
Retrofitting for Energy Conservation

William H. Clark II



McGraw-Hill

New York San Francisco Washington, D.C. Auckland Bogotá
Caracas Lisbon London Madrid Mexico City Milan
Montreal New Delhi San Juan Singapore
Sydney Tokyo Toronto

Contents

Preface vii

Introduction	1
Part 1 The Methods	
Chapter 1. The Domestic Water System	13
Chapter 2. Building Envelope	27
Chapter 3. Ventilation and Infiltration Control	43
Chapter 4. Lighting Projects I	83
Chapter 5. Lighting Projects II	99
Chapter 6. Heating and Cooling Systems	115
Chapter 7. Central Systems	159
Chapter 8. Electrical Projects	197
Chapter 9. Architectural Concepts	207
Chapter 10. Controls	231
Part 2 The Projects	
Chapter 11. Water and Steam System Projects	251
Project 1 Replacing inefficient hot-water heaters	251
Project 2 Steam-trap replacement	256

Chapter 12. Building Projects	259
Project 3 Attic insulation	259
Project 4 Motor projects	265
Chapter 13. HVAC Projects	269
Project 5 Heat-pump retrofits	269
Project 6 Dedicated air-handling unit	271
Project 7 More efficient HVAC units	275
Chapter 14. Lighting Projects	277
Project 8 Security lighting	277
Project 9 Reflective inserts	282
Project 10 Fixture relamping	285
Project 11 Interior lighting controls	288
Project 12 Exterior lighting controls	290
Chapter 15. Controls Projects	293
Project 13 Cooling-tower fan controls	293
Project 14 Programmable thermostats	297
Project 15 Time clock control of motors	300
Chapter 16. Auditing Existing Buildings	305
Chapter 17. The Building Plan Review Audit	335
Chapter 18. Energy Tips and Tricks	347
Chapter 19. The HVAC Design Process	383
Chapter 20. Numerical Analysis Techniques	397
Epilogue	415
Glossary	419

Index

- Air curtain, 38, 220
- Baseboard heaters, 41
- Below-grade construction, 210–211
- Bin analysis, 410–413
- Bleed off, 66
- Boiler:
 - blowdown, 160, 176, 184–185
 - boiler combustion rate, 14, 163–164
 - feedwater preheating, 22
 - maintenance, 174–176, 181–183, 194–196
 - operation, 141–142, 179–180
 - performance ratings, 182
 - stack temperatures, 165, 180–181
 - staging, 164, 246
 - waste heat recovery, 185, 186
- Building loads:
 - calculations, 4, 157, 338, 342
 - diversity factors, 28
 - profile, 27, 221–222, 385–389
- Carbon dioxide, ix, 44, 131, 142, 357
- Carbon dioxide sensors, 62, 71
- Ceiling space projects, 219, 223, 352
- Chemical treatment:
 - cooling towers, 66
- Chilled water systems:
 - heat recovery, 164
 - performance criteria, 154
 - protection, 155, 159–161, 236–237
 - rebuilt, 153–155
 - staging chillers, 165–166, 235, 246
 - temperature reset, 131, 235–236, 241–242
- Cold air system, 76
- Color Rendering Index, 85
- Compact fluorescent lamps, 85, 104–105, 319–321
- Compressed air, 178–179
- Condenser water loop (*see* Cooling tower)
- Controls:
 - air handlers, 54, 129, 369, 378–380
 - change over controls, 244–245
 - demand reset, 130, 237–238
 - load leveling, 242–243
 - survey, 47, 327–329
 - two-stage controls, 243–244
- Cooling tower:
 - fan controls, 134, 166, 293–297
 - maintenance, 167, 177–178
 - staging, 168, 188, 189
 - water control, 133, 176
- Daylighting, 30, 99–101, 211, 217, 338, 361
- DBase, 400–413
 - data base, 401–402, 406–407
 - data entry screen, 402–404
 - printing out data, 407–410
 - program module, 404–406
- Decoupled system, 80
- Dehumidification, 40, 59, 62, 77
- Dessicant dehumidification, 73, 81, 191
- Desuperheater, 24, 25, 70, 185, 187
- Direct expansion (DX) units, 125–126, 145–146, 189–191, 244
- Door closer, automatic, 8, 38, 46, 355
- Duct:
 - air velocities, 55, 139–140, 214, 218
 - cleaning, 132–133, 365

Duct (*Cont.*):

- condensation, 73
- insulation, 74, 75-76
- seal leaks, 56
- test & balance, 140

ECM (energy-conservation measures), 8

Economics, viii

Economizer cycle, 15, 73

Economy cycle, 64, 65

Electric:

- neutral leg losses, 201, 203-204
- power densities, 216
- power factor correction, 204-205
- resistance heating, 23, 121-122
- systems analysis, 200, 306

Elevator controls, 200-201

Energy:

- audit, 305-308
- awareness program, 1, 4
- conversion factors, xii

Energy Policy Act of 1992, 84, 418

Engineering:

- design fees, 4

Enthalpy sensor, 67-68

Envelope, building, 54

Exhaust hoods, 30, 49, 61

Fans, 116-117

Fan coil unit:

- four pipe, 61-62
- two pipe, 50-51

Filter, 239

- activated carbon, 63

Flat plate heat exchanger, 65, 73, 79, 80, 237

Floors:

- insulation, 39

Fluorescent lights:

- analysis, 85, 217, 321-323
- energy use, 7, 85

Free cooling (*see* Economy cycle)

Freon ban, viii, x, 415-441

Friction losses:

- pipng, 19-20

Frost protected foundations, 230

Functional space size, 212-214, 215-216

Furnace, 126

Gas-driven chillers, 194

Ground source heat pump, 148, 149-151, 156-157, 311-312

Harmonics, 203, 206

Heat exchanger, 14

(*See also* Flat plate heat exchanger)

- enthalpy wheel, 79, 80
- heat pipes, 79
- run around coils, 79
- shell-in-tube, 25

Heat pump, 121, 269-271

Heat tape or heat tracing, 20, 254, 349, 350

Heavy wall construction, 41

HID lights, 85

Hot deck, 62, 138

Hot gas bypass, 122

Hot water:

- reset, 14, 15, 59
- service quantities, 25
- storage temperature, 13

Humidity survey, 64

Hydronic system:

- air separation, 134-135
- balancing system, 135-136
- bladder tanks, 135
- controls, 137-138, 169-170, 183-184
- transmission losses, 162

HVAC:

- electrical loads, 198
- rooftop air handler, 331-332
- systems, 192-193, 271-275, 275-276, 339-341, 389-395

IAQ (*see* Indoor Air Quality)

Incandescent lights, 85

Indoor Air Quality:

- humidity rules, ix
- psychological effects, ix
- regulations, ix

Induction units, 58

Inrush current, 6

Insulation:

- ceiling, 31
- partitions, 40
- pipng, 15, 19

Inventory, 3

Kitchen, 15, 29-30, 48, 215, 224, 242, 309, 330

- Landscape use, 36–37, 223, 352
- Latent loads, 30, 32
- Laundry, 15, 38, 242, 348
- Leak inspections, 13
- Lighting:
 - controls, 90, 96–98, 106, 281, 288–290, 310
 - energy use, 92, 101–103, 107–109
 - exit sign replacement, 317–318
 - exterior lighting, 290–291, 309
 - layout, 87–89
 - levels, 88, 107
 - power allowances, 110–114
 - relamping project, 285–288, 334, 398
 - security lighting, 277–282
 - use schedule, 84
- Louvers, gaskets, 47, 51

- M & O's (maintenance and operational projects), 8
- Maintenance:
 - HVAC, 127
 - low cost projects, 7, 8
 - program, 2, 3, 240
- Management, director, 84
- Metal studs & framing, 208–209, 227
- Motor:
 - balancing, 201–202
 - efficiencies, 302
 - maintenance, 202
 - replacement, 265–268, 323–325, 399
 - time clock control, 300–304

- Optimized start-stop, 223–234
- Outside air:
 - calculations, 52, 332–334
 - controls, 71, 141, 142–143
 - sensors, 53, 354
 - standards, 53, 340

- Payback:
 - present value, xi, 6, 23
- Peak load reduction, 199–200
- Piping (*See also* Hydronic system)
 - hot & chilled water, 136–137
- Point-of-use applications, 220–221
- Precooler, 143, 365
- Preheat coil, 77
- Pressurization, 44–45, 223–225, 226–227
- Primary/secondary loop, 234–235

- Productivity, 85, 101, 217, 362, 363, 364, 370
- Pump laws, 137

- Radiant:
 - barrier, 39, 228–230, 352
 - energy, 28, 42, 218–219, 229–230
- Radiator maintenance, 16
- Random start-stop, 58
- Reflective inserts, 282–285
- Refrigerant:
 - survey, 47
- Reverse return loop, 94–95
- Roof:
 - color, 37, 221
 - curbs, 55
 - insulation, 259–264, 325–327
 - sprinkler system, 42
- R-value, 260–261

- Savings:
 - accumulating factors, xii
- Sick building syndrome, 59, 77, 356, 365
(*See also* Carbon dioxide, Outside air)
- Smoking area, 51
- Solar:
 - film or screens, 32
 - water heating, 23–24, 348, 375
- Sound attenuation, 74
- Stack effect, 36, 44
- Standby losses, 252
- Steam:
 - distribution system, 168–169, 173–174
 - generator, 14, 22
 - replacement, 256–258
 - traps, 171–173
- Submetering, 216–217
- Sump pump level control, 17
- Switching, 30

- Thermal effects:
 - bridging, 41, 207–210, 227
 - mass effects, 41, 60, 144, 148, 211–212, 238, 340
- Thermal storage, 247–248
- Thermostats, 117–120, 146, 222, 223, 297–300, 352
- Time clocks:
 - air conditioning, 126–127, 151, 153, 231–232, 310

- Time clocks (*Cont.*):
 - circulating pump, 18, 121
 - lighting, 91
 - outside air, 72
 - ventilation systems, 57
 - water heater, 15
- Transformers, 215
 - sizing, 204
- Two speed motor, 69, 79, 134, 144, 156, 167, 189, 237
- Unit ventilator, 57
- Utility:
 - demand rate, 5, 238-239
 - exhaust fans, 49
 - rate analysis, xi, 4-6, 198-199
- U-values, 31
- VAV (*see* Variable air volume)
- Vapor barrier, 18, 32, 69-70
- Variable air volume:
 - air flow, 56, 126-127
 - reheating, 163, 170
 - retrofitting, 78, 124-125, 130, 170-171
- Variable frequency drive, 170
- Variable speed pumping, 156, 206
- Ventilation, 34, 36, 45-46, 68
- Vestibule, 29
- Visual comfort, 86, 90-91, 95, 100, 106
- Warm up cycle, 58, 59
- Waste heat recovery, 38, 191-194
- Water heater, 251-256
 - blanket, 16
 - controls, 330-331, 337, 348
 - electric, 23
 - equipment efficiency ratings, 21
 - inefficiencies, 22
 - instantaneous, 20
 - use per occupant, 17
- Water softener, 21-22
- Water source heat pump, 147, 151-153, 227
- Weather stripping, 8, 359
- Water-to-water efficiency, 136
- Window:
 - air conditioning units, 47
 - double paned, 28, 208
 - shading devices, 31, 351, 353
 - storm, 28, 351
 - shading coefficients, 34
 - u-values, 29
 - yearly heat gains, 35
 - yearly heat losses, 33
- Xeriscaping, 349
- Zonal cavity method, 89

ABOUT THE AUTHOR

WILLIAM H. CLARK is a mechanical, plumbing, structural, electrical, and lighting engineer who has been active in renovation projects throughout his career. An expert on energy-efficient materials and designs, he is a nationally known authority on retrofitting for energy conservation. Mr. Clark has written articles for numerous trade and technical journals, as well as several computer programs to model energy conservation strategies.

Developing a Research Agenda for Retrofitting Sustainability. Contents. Introduction. Energy conservation for urban housing. Energy conservation in commercial, institutional and industrial buildings. Climate change and built environment. Water management. Energy-relevant factors of building envelopes include window-wall ratio, insulation levels of walls and roofs, the thermal resistance and solar heat gain coefficient of windows, the degree of air-tightness to prevent unwanted exchange of air between inside and outside, and the presence or absence of operable windows. Almost 85% of energy-conserving projects are retrofits, according to the National Association of Homebuilders. Retrofitting for Energy Conservation gives you the tools you need to meet this demand with step-by-step help in retrofitting any residence or light commercial building for energy savings. From assessing the challenge and offering the client options through initial Almost 85% of energy-conserving projects are retrofits, according to the National Association of Homebuilders. Retrofitting for Energy Conservation gives you the tools you need to meet this demand with step-by-step help in r... Energy Conservation Retrofitting Construction. Program Management Services. Proposal to provide energy conservations retrofitting and construction program. Management assistance nationwide to publicly and privately operating facilities. Before entering in an ESCO Performance Contract, Facilities. Consultant supply world's best Energy Conservation Retrofitting Construction Projects Management Services to several cities across the United States. Demands for our services have increased tremendously owing to the great experiences like:

- Experience developing value propositions with cost/benefit analyses for products and services.